

Red Sasso Bracelet

Design by VBS

Red and Black always popular no matter the season.

SKILL LEVEL:

Tools:
Side Cutter

Wire:
WS-SFW01910SLV Soft Flex 49 Strands Wire
.019 dia

Or you can use any wire you have already.

Components



Part SKU	Quantity	Item Name
F-PW-CLTG-BAR-AS	1	12mm Pewter Bar and Ring Toggle, Antique Silver Plate
F-PW-SPC-HSH04-AS	12	4mm Antique Silver Plated Heishi Spacer Bead
F-SS-CRIMP-COV4	2	.925 Sterling Silver Crimp Cover, 4mm
F-SS-CRIMPTW-2X2	2	Sterling Silver Twisted Crimp, 2x2mm 1mm ID
F-SS-WIREPROT021	2	.925 Sterling Silver Wire Protectors .021, Per Piece
SASSO-16-9	5	Venetian Bead Pebble 16mm, Clear Red
SASSO-20-9	1	Venetian Bead Pebble 20mm, Clear Red Center
SCH-RN-06-OP16	8	Opaque Black Murano Glass Round Bead, 6mm

Instructions:

Step 1. Cut a length about 12 inches of the wire. Lay the bracelet out on table. Begin with the center 20mm pebble then in a repeating pattern, add a Heishi Spacer followed by a solid black 6mm bead. The last pebble is followed by 2 6mm beads. Note from the photo that the 6mm closest to the clasp does not have a Heishi. That is so you can run the wire back through the first 6mm black bead.

Step 2. To finish the bracelet, on one side thread the crimp tube onto your wire and then through the wire protector. In the center of the horseshoe shape wire protector. Push the wire back through the crimp tube.

Step 3. Crimp the crimp bead just at the end of the wire protector and slide the wire through the 6mm bead. Cut off the excess just after the first black bead.

Step 4. Do the same for the other side.

Hint: I put the bar side of the toggle on first I can hold onto the ring to get the wire snug.